



MR112/MR112N MRseries MR112A/MR112NA

Two-way Loudspeaker System

FEATURES

- High quality components, high strength plywood housing
- Small height, take small space
- Can be placed on stage, can be hung
- Applications: Stage monitor

产品特征

- 高质量单元配置,高强度夹板箱体
- ●高度尺寸小,占用空间小
- ●可舞台摆放、可吊挂

适用范围


●舞台监听


MR112 is compact, small height size, coaxial, 12" two-way full range monitor series speaker with different configurations, has balanced and real sound quality. Configuration:1x12" high efficency mid-bass unit and 1x1" exit throat 44mm voice coil HF driver with special designed horn. The cabinet is made of multilayer composite plywood with wear-resistant polyurea paint. The model with N is a neodymium magnetic unit, and the model with A is active.

MR112是不同配置,12"同轴结构设计的两分音舞台监听系列音箱,结构紧凑,高度尺寸小,音质平衡衡、真实。单元配置:1只12"高效率中低音单元和1只1"喉口44芯驱动器,配置专门设计的号角。箱体采用多层复合夹板,聚脲喷涂制作。型号带N为钕磁单元、型号带A为有源。



CONFIGURATION





MODEL FREQUENCY RESPONSE(-3dB) FREQUENCY RESPONSE(-10dB) DRIVERS

RATED POWER
SENSITIVITY
MAXIMUM SPL
IMPEDANCE
DISPERSION(-6dB)
CROSSOVER FREQUENCIES
INPUT CONNECTORS
PACKAGE SIZE
NET WEIGHT
GROSS WEIGHT

Page 29

MR112/ MR112N

75Hz-18kHz

70Hz-20kHz

 1×12 "(300mm)/3"voice coil LF

 $1\times1"$ (25mm)/1.7"voice coil HF

300W RMS,1200W peak

97dB 1watt/1 metre

122dB continuous,128dB peak

8 ohms nominal

70°×40°

2.3kHz passive

2×Speakon NL4

560mm×425mm×545mm

24 kg/pc; 20kg/pc

27 kg/pc; 23kg/pc

MR112A/ MR112NA

75Hz-18KHz

70Hz-20kHz

 1×12 "(300mm)/3"voice coil LF

 $1\times1"$ (25mm) / 1.7"voice coil HF

600W/8Ω

--

122dB continuous,128dB peak

...

 $70^{\circ} \times 40^{\circ}$

INPUT TYPE: Balanced Differential line

www.fdbaudio.com

560mm $\times 425$ mm $\times 545$ mm

26 kg/pc; 22kg/pc 29 kg/pc; 25kg/pc

I I