

# CM73-IP

## Avonic PTZ Camera 30x Zoom IP

The Avonic CM73 is a premium-quality PTZ camera that includes a rich feature set usually found only on broadcast-grade cameras including PoE, low latency 3G-SDI and balanced audio embedding.

Optional premium features consist of SRT streaming, a Tally light and a customizable Color Matrix.

The camera with IP, HDMI and 3G-SDI outputs is designed for fixed installations and works very well in low light conditions.

The camera is equipped with high quality components like a Panasonic high SNR CMOS sensor with digital noise reduction and a High Quality glass lens. Control the camera over IP, RS232 or RS485 with any controller with VISCA or PELCO support.



## Features

### Lens

High-quality glass lens, 30x optical zoom and 58.9° horizontal field of view.

### Low light

High SNR CMOS combined with digital noise reduction for a clear picture even under very low light conditions.

### Full HD 1080p60

The camera has a Full HD resolution of 1920 x 1080p60 and achieves a pristine image quality.

### IP-features

The camera can be powered using PoE (802.3af) and can be accessed by webGUI, controlled by VISCA over IP/ Onvif and stream the video.

### DUAL low latency IP-Stream

H265, H264, optional SRT and MJPEG compression at a bitrate up to 40Mbit enabling Full HD video stream by ultra-low latency over RTSP, RTMP, UDP, Unicast and Multicast.

### Outputs

3G-SDI, HDMI, USB 2.0 (1080p30) and IP.

### Control

Control the camera with common protocols: VISCA, Pelco-D/P via RS232, RS485, IP(VISCA), Onvif or IR, remote control included. Supports up to 255 presets with 0.1° accuracy and High Speed Pan Tilt function.

### Audio embedding

Balanced audio input with embedding into IP stream, SDI and HDMI outputs. Includes configurable audio offset.

### Optional Premium features

SRT streaming, Tally light, configurable Color Matrix. License AV-LC70-1 sold separately.

## Applications

- Education
- Churches
- Video Conferencing
- Healthcare
- Broadcasting
- Courtroom
- Live Events
- And more

# SPECIFICATIONS

## Camera

Video Systems	1920x1080/ 1280x720 p60/ 50/ 30/ 25/ 59.94/ 29.97 i60/ 50/ 59.94
Sensor	1/3" CMOS, 2.12mp, 16:9
Shutter	Auto, Manual, 1/25 ~1/10000
Scanning mode	Progressive, Interlaced (not over IP)
Zoom/Aperture/Focal length	30x optical/ F1.8-F11/ 4.3-129.0 mm
Minimal Illumination	0.05 LUX
White Balance	Auto, Manual, OnePush, 2400K-7100K in steps of 100K
Backlight Compensation	supported
Digital Noise Reduction	2D & 3D DNR
Signal Noise Ratio	>55 dB
Horizontal FOV wide ~ tele	58.9° ~ 2.11°
Vertical FOV wide ~tele	45.3° ~ 1.61°
Horizontal rotation	-170° ~ +170°
Vertical rotation	-30° ~ +90°
Pan speed range	1.7 ~ 100°/s
Tilt speed range	1.7 ~ 70°/s
H&V image flip	supported
Number of presets	255
Preset accuracy	0.1

## IP features

Video coding standard	H.265 / H.264 / MJPEG
H.265 Profiles	main
H.264 Profiles	main, base, high
Main stream resolution	1920x1080 / 1280x720
Main stream max frame rate	60fps
Main stream bitrate	64 ~ 40960 Kbps
Sub stream resolution	320x180 / 320x240 / 640x360 / 1280x720 / 1920x1080
Sub stream max frame rate	30fps
Sub stream bitrate	64 ~ 40960 Kbps
Video bitrate type	Variable, Fixed
Support protocols	RTSP, RTMP, ONVIF, SRT, Multicast, Unicast
Audio standard	AAC / mp3 / G.711A
Audio bitrate	32, 64, 96, 128 Kbps
Audio sample rate	16, 32, 44.1, 48 Khz
Audio line in	balanced audio line in via 5-way Phoenix connector.

## Input/Output Interface

HDMI output	1.4
SDI output	3G-SDI, SMPTE 425M level A, 10-bit YCbCr 4:2:2
USB Output	USB 2.0 (max. 1080p30)
Network interface	RJ45 100Mbps
Serial communication	RS232 mini DIN-8, RS485 2pin Phoenix
Serial control protocol	VISCA, PELCO-P, PELCO-D
IP control protocol	VISCA OVER IP, Onvif

## General specifications

Input voltage	12V
PoE	PoE 12W (802.3af)
Power consumption	12W
Power supply	12V2A
Power connector	EIAJ-4 - Philmore 255 plug
Operating temperature	-5°C ~ 40°C
Storage temperature	-20°C ~ 60°C
Operating humidity	20% ~ 95% non-condensing
Bottom fastening screw thread	1/4" 20 UNC
Color	Black, White
Dimensions product wxhxd	133 x 180 x 149 mm. excl. connectors
Weight product	1.5 kg
Dimensions box	26 x 24 x 24 cm
Weight box	2.4 kg
Included	power adapter, remote control, RS232 cable, RS485 2-way Phoenix connector, Balanced Audio Line-In 5-way Phoenix connector

## Versions

Black	CM73-IP-B
White	CM73-IP-W

